


# HR-8417

## 4" Low Voltage Downlight Trim



Fixture Type:

Catalog Number:

Project:

Location:

### PRODUCT DESCRIPTION

Adjustable gimbal ring trim with dual pin axis.  
For use with HR-8400 series low voltage housings.

### FEATURES

- Gimbal ring, 25° adjustment from vertical recessed downlight
- Center lamp holder allows lamp to be tilted up to 25° from vertical
- The supplied clear glass lens can be replaced with one lens accessory
- Handles surfaces up to 3/4" thick
- 5 year WAC Lighting product warranty

### ORDER NUMBER

Model # Finish

HR-8417	<b>BK</b>	Black
	<b>BN</b>	Brushed Nickel
	<b>CB</b>	Copper Bronze
	<b>WT</b>	White

Model # Finish

**HR-8417** -

Example: **HR-8417-BK**

### SPECIFICATIONS

**Construction:** Durable stamped metal construction.  
Three heavy gauge retention clips firmly hold trim to housing.

**Lamp:** Utilizes LED or Halogen 12V MR16 lamps (order separately).  
50W or 75W maximum, see individual housing for wattage rating.

**Finish:** Abrasion resistant powder coat painted or plated metal finish. Available in Black (BK), Brushed Nickel (BN), Copper Bronze (CB) and White (WT).

**Standards:** UL & CUL Listed, Suitable for damp locations

### ACCESSORIES

LENS-16- Color Lens	<b>AMB</b>	Amber	<b>LENS-16-UVF</b>	UV Filter
	<b>BLU</b>	Blue	<b>LENS-16-FR</b>	Frosted Lens
	<b>GRN</b>	Green	<b>LENS-16-SPR</b>	Spread Lens
	<b>RED</b>	Red	<b>LENS-16-BEL</b>	Beam Elongating Lens
	<b>YEL</b>	Yellow	<b>LENS-16-HCL</b>	Honeycomb Louver

### 4" Low Voltage Housings (Required)

	Model	Voltage	Transformer	Output	Installation	Rating
	<b>HR-8402E</b>	120V	Electronic	12V, 50W max	New Construction	Non-IC
	<b>HR-8402HL*</b>	120V	Magnetic	12V, 75W max	New Construction	Non-IC
	<b>HR-8403</b>	<b>H</b> 120V <b>HF</b> 277V	Magnetic	12V, 50W max	New Construction	IC Airtight
	<b>HR-8402</b>	<b>H</b> 120V <b>HF</b> 277V	Magnetic	12V, 50W max	New Construction	Non-IC
	<b>HR-8401E</b>	120V	Electronic	12V, 50W max	Remodel	Non-IC
	<b>HR-8401</b>	<b>H</b> 120V <b>HF</b> 277V	Magnetic	12V, 50W max	Remodel	Non-IC

\*Not Compatible with HR-D418 or HR-D418-S Non-IC housings require 3" of clearance from insulation on all sides.

Accommodates ceiling thickness of up to 3/4" for remodel & 3/4" for new construction.

### WAC Lighting

www.waclighting.com

Phone (800) 526.2588 • Fax (800) 526.2585

### Headquarters/Eastern Distribution Center

44 Harbor Park Drive • Port Washington, NY 11050

Phone (516) 515.5000 • Fax (516) 515.5050

### Western Distribution Center

1750 Archibald Avenue • Ontario, CA 91760

Phone (800) 526.2588 • Fax (800) 526.2585