


R-432

4" Line Voltage Downlight Trim



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Recessed trim gimbal ring - 20° adjustment from vertical.
For use with R-400 series Line voltage downlight housings.

FEATURES

- Durable stamped metal construction
- Retention clips hold trim firmly to housing
- Abrasion resistant powder coat paint or plated metal finish
- Handles surfaces up to 3/4"
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Durable stamped metal construction.
Three heavy gauge retention clips firmly hold trim to housing.

Lamp: Utilizes LED PAR20 lamp or medium base incandescent or 4-pin CFL lamps. Incandescent lamps are rated for up to 50W watts max. Compact Fluorescent lamps are rated for 13 watts max. Lamps are ordered separately.

Finish: Abrasion resistant powder coat painted or plated metal finish. Trim is available in Brushed Nickel (BN), Copper Bronze (CB) or White (WT).

Standards: UL & CUL Listed. Suitable for damp locations.

ORDER NUMBER

Model Finish

R-432	BN	Brushed Nickel
	CB	Copper Bronze
	WT	White

R-432 -

Example: R-432-CB

FINISHES



LED PAR20 LAMP (ORDER SEPARATELY)

PAR20LED-10N30	BK	Black
	WT	White

4" Line Voltage Housings (Required)

	Model	Installation	Rating	Voltage
<p>IC-Rated New Construction</p>	R-4025-N-ICA	New Construction	IC – Airtight Ready	120V
<p>Non-IC New Construction</p>	R-4005-N-A	New Construction	Non-IC – Airtight Ready	
<p>Non-IC Remodel</p>	R-4015-R-A	Remodel	Non-IC – Airtight Ready	

Non-IC housings require 3" of clearance from insulation on all sides.
Accommodates ceiling thickness of up to 3/4" for remodel & 3/4" for new construction.

WAC Lighting

www.waclighting.com
Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive • Port Washington, NY 11050
Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center

1750 Archibald Avenue • Ontario, CA 91760
Phone (800) 526.2588 • Fax (800) 526.2585