



Description	A wider path and spread light that is unobtrusive in the landscape. Coordinates with our 15410 & 15470 Domed Roof series.																				
Ordering Guide & Finish	15310 AZT - Textured Architectural Bronze 15310 AZT6 - Same as 15310 AZT. Bulk packed in 6 (unbreakable master) 15310 BE - Beach 15310 BKT - Textured Black																				
Housing	Cast Aluminum																				
Lamp Base	12V T5 wedge base socket																				
Supplied Lamp	16.25-W(VA) 921X (17025) Xenon light source Power usage at 12V AC input VA MAX: 16.25-W(VA)																				
Incandescent Lamp Options	11.6-W(VA) 912X (17023) 6.5-W(VA) 918X (17022) 4-W(VA) 901X (17021)																				
LED Lamp Options	2W (18039-18041) see page 159 Compares up to 16W Xenon																				
Wiring	24" of usable #18-2, SPT-1-W leads. Cable connector supplied																				
Mounting Acces. Included	8" In-ground stake																				
Optional Acces.	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket																				
Integrated LED Options	15810 - on Page 17																				
Photometric with Supplied Lamp	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="font-size: small;">Distance from Light</td> <td style="text-align: center;">1'</td> <td style="text-align: center;">2'</td> <td style="text-align: center;">3'</td> <td style="text-align: center;">4'</td> <td style="text-align: center;">5'</td> <td style="text-align: center;">6'</td> <td style="text-align: center;">7'</td> <td style="text-align: center;">8'</td> <td style="text-align: center;">9'</td> </tr> <tr> <td style="font-size: small;">Footcandles</td> <td style="text-align: center;">8</td> <td style="text-align: center;">4.1</td> <td style="text-align: center;">1.6</td> <td style="text-align: center;">.5</td> <td style="text-align: center;">.4</td> <td style="text-align: center;">.1</td> <td style="text-align: center;">-</td> <td style="text-align: center;">-</td> <td style="text-align: center;">-</td> </tr> </table>	Distance from Light	1'	2'	3'	4'	5'	6'	7'	8'	9'	Footcandles	8	4.1	1.6	.5	.4	.1	-	-	-
Distance from Light	1'	2'	3'	4'	5'	6'	7'	8'	9'												
Footcandles	8	4.1	1.6	.5	.4	.1	-	-	-												

Denotes fixture is compatible with incandescent or LED lamps.

INCANDESCENT / LED 12V HYBRID PATH & SPREAD



INCANDESCENT/LED 12V HYBRID PATH & SPREAD

P

	15410 AZT, BE - DOME PATH LIGHT	15470 AZT, BBR, BE, BKT - 6" DOME PATH LIGHT																																								
Description	A shorter version of our popular 15310 designed for use with lower planting and smaller garden areas. Coordinates with our 15310 & 15470 Domed Roof series.	A popular look with a smaller 6" shade. Coordinates with our 15310 & 15410 Domed Roof series.																																								
Ordering Guide & Finish	15410 AZT - Textured Architectural Bronze 15410 BE - Beach	15470 AZT - Textured Architectural Bronze 15470 BBR - Bronzed Brass 15470 BE - Beach 15470 BKT - Textured Black																																								
Housing	Cast Aluminum	Cast Aluminum, Cast Brass																																								
Lamp Base	12V T5 wedge base socket	12V T5 wedge base socket																																								
Supplied Lamp	16.25-W(VA) 921X (17025) Xenon light source Power usage at 12V AC input VA MAX: 16.25-W(VA)	16.25-W(VA) 921X (17025) Xenon light source Power usage at 12V AC input VA MAX: 16.25-W(VA)																																								
Incandescent Lamp Options	11.6-W(VA) 912X (17023) 6.5-W(VA) 918X (17022) 4-W(VA) 901X (17021)	11.6-W(VA) 912X (17023) 6.5-W(VA) 918X (17022) 4-W(VA) 901X (17021)																																								
LED Lamp Options	2W (18039-18041) see page 159 Compares up to 16W Xenon	2W (18039-18041) see page 159 Compares up to 16W Xenon																																								
Wiring	30" of usable #18-2, SPT-1-W leads. Cable connector supplied	24" of usable #18-2, SPT-1W leads. Cable connector supplied																																								
Mounting Acces. Included	8" In-ground stake	8" In-ground stake																																								
Optional Acces.	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket																																								
Integrated LED Option	15811 - on Page 17	15870 - on Page 16																																								
Photometric with Supplied Lamp	<table border="1"> <tr> <td>Distance from Light</td> <td>0'</td><td>1'</td><td>2'</td><td>3'</td><td>4'</td><td>5'</td><td>6'</td><td>7'</td><td>8'</td> </tr> <tr> <td>Footcandles</td> <td>22.0</td><td>9.6</td><td>4.0</td><td>1.1</td><td>.03</td><td>0.1</td><td>-</td><td>-</td><td>-</td> </tr> </table>	Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'	Footcandles	22.0	9.6	4.0	1.1	.03	0.1	-	-	-	<table border="1"> <tr> <td>Distance from Light</td> <td>0'</td><td>1'</td><td>2'</td><td>3'</td><td>4'</td><td>5'</td><td>6'</td><td>7'</td><td>8'</td> </tr> <tr> <td>Footcandles</td> <td>6.17</td><td>4.85</td><td>4.34</td><td>2.51</td><td>1.58</td><td>1.35</td><td>0.77</td><td>0.43</td><td>0.28</td> </tr> </table>	Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'	Footcandles	6.17	4.85	4.34	2.51	1.58	1.35	0.77	0.43	0.28
Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'																																	
Footcandles	22.0	9.6	4.0	1.1	.03	0.1	-	-	-																																	
Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'																																	
Footcandles	6.17	4.85	4.34	2.51	1.58	1.35	0.77	0.43	0.28																																	

Denotes fixture is compatible with incandescent or LED lamps.