

12V LED ACCENT

WALL WASH



16070 AZT, BBR, BKT

WALL WASH ACCENT LIGHT



15861 AZT, BBR, BKT

	16070 AZT, BBR, BKT		15861 AZT, BBR, BKT	
Kelvin	2700K Warm White		3000K Pure White	
Ordering Guide & Finish	16070 AZT27R 16070 BBR27R 16070 BKT27R	16070 AZT30R 16070 BBR30R 16070 BKT30R	15861 AZT27R 15861 BBR27R 15861 BKT27R	15861 AZT30R 15861 BBR30R 15861 BKT30R
Housing	Cast Aluminum, Cast Brass		Cast Aluminum, Cast Brass	
Light Source	8 Integrated High Output Nichia® LEDs, tightly binned for color uniformity, and constant current driver		8 Integrated High Output Nichia® LEDs, tightly binned for color uniformity, and constant current driver	
Beam Spread	Vertical = 80° Horizontal = 100°		Vertical = 108° Horizontal = 111°	
Color Temp. (CCT) & CRI	2700K (-55/ +90) / 80s CRI 3000K (-52/+122) / 80s CRI		2700K (-55/+90) / 80s CRI 3000K (-52/+122) / 80s CRI	
Power Usage at 12V AC Input VA and Watts	4.3 W, 5.8 VA		4.3 W, 5.8 VA	
Operating Voltage Range	9V-15V AC/DC with no loss in output due to constant current technology		9V-15V AC/DC with no loss in output due to constant current technology	
Lumen Maint.	Tested to an L-70 of 40,000 hours		Tested to an L-70 of 40,000 hours	
Delivered Lumens & Efficacy	2700K = 294 Lm 2700K = 67 Lm/W	3000K = 302 Lm 3000K = 73 Lm/W	2700K = 294 Lm 2700K = 67 Lm/W	3000K = 302 Lm 3000K = 73 Lm/W
Wiring	63" of usable #18-2, SPT-1W leads. Wire connectors supplied.		64" of usable #18-2, SPT-1W leads. Wire connectors supplied.	
Mounting Access. (Included)	8" slotted in-ground stake		8" slotted in-ground stake	
Optional Accessories	15601 – Surface Mounting Flange 15607 – Surface Mounting Bracket 15609 – Junction Box Mounting Bracket 15647 – 90° Elbow 15645, 15656, 15657, 15658 or 15570 – Stems		15601 – Surface Mounting Flange 15607 – Surface Mounting Bracket 15647 – 90° Elbow 15645, 15656, 15657, 15658 or 15570 – Stems	
Notes	Fully adjustable knuckle. Brass will naturally patina over time.		Fully adjustable knuckle. Brass will naturally patina over time.	
Fixture Photometric (fc)*	Distance from Wall	0' .5" 1' 2' 3' 4' 5.5'	Distance from Wall	0' .5" 1' 2' 3' 4' 5.5'
	2"	47.00 39.40 16.20 1.30 0.25 0.22 0.19	2"	51.20 45.50 30.00 7.10 1.90 0.68 0.30
	4"	12.5 12 10.8 5.1 1.8 0.54 0.17	4"	12.9 12.9 11.8 7.9 4.2 1.6 0.7

*Values stated for 3000K. -10% for 2700K.