Product Name:	ABT-23S-TS
Description	TempLog Premier Solid Door Laboratory Refrigerator
Description:	23 Cu. Ft. capacity
	One swing solid door, self-closing, right hinged, not reversible
	Microprocessor temperature controller
	Adjustable operating temperature range: 1°C - 10°C
	Touch Screen Digital Temperature Display and Alarm Module
	Password-protected control panel
	Sample simulated digital temperature display; .1° Resolution, adjustable
	temperature display in Celsius or Fahrenheit
	Active temperature scale bar display
	Resettable 1-point min/max history
	Digital 24-hour temperature chart
	Temperature data logging
	USB port for data transfer and software updates
	Real-time operational display clock
	4-20mA output
	Electronic troubleshooting guide
	Electronic QR Code to access Owner's Manual & technical support
	contact information
	Adjustable alarm volume
	Audible and visual high/low temperature alarms
	Sensor error alarm
	Power failure alarm
	Door ajar alarm
	Low battery alarm
	Operation indicator
	Alarm validation (audible, visual, and remote alarm)
	Alarm mute with ring back
	Remote alarm contacts
	Four adjustable shelves (adjustable in 1/2" increments)
	Keyed door lock
	Magnetic door gasket for positive seal
	Heavy duty door handle
	LED interior lights are safety shielded and switch controlled
	Casters with footed brake
	Probe access port (3/8")
	White powder-coated steel exterior and interior
	CFC-free refrigerant (R134a), foam insulation and packaging
	Three year parts and labor warranty, plus an additional two year compressor
	parts warranty
	Quality certified with 100% unit temperature testing
	Exterior dimensions: 26 7/8"W x 34 ¾"D x 79 ¾"H
	Cycle defrost
	115V, 60 Hz, 6 Amps, 3/8 HP
	UL/C-UL listed
	Shipping weight: 321 lbs.