

Product Name:	ABT-AFPP-23
Description:	<p>Premier Stainless Steel Auto Defrost Laboratory Freezer 23 Cu. Ft. Capacity One swing stainless steel door Multi-Point temperature mapping via NIST traceable data acquisition, 15 probes in air and 3 probes in sample solution for 360 minutes with temperature readings every 60 seconds Digital Temperature Display & Alarm Module: Microprocessor Temperature Controller Adjustable operating temperature range: -15°-25°C Digital Temperature Display and Alarm Module Sample simulated digital temperature display; .1° Resolution Adjustable temperature display in Celsius or Fahrenheit Audible and visual high/low temperature alarms Sensor error alarm Power failure alarm Resettable 1-point Min/Max History Remote alarm contacts Alarm validation (audible, visual, and remote alarm) Alarm mute with ring back Three shelves (adjustable in ½" increments) Keyed door locks Magnetic door gasket for positive seal Recessed door handle Swivel casters (adds 5" to height; included in dimensions) Interior light Probe access port (3/8") 300 Series stainless steel interior/exterior High density urethane foam cabinet and door insulation HFC-free refrigerant (R290a), foam insulation and packaging Quality certified with 100% unit temperature testing Two year parts and labor warranty, plus an additional three year compressor parts warranty Exterior dimensions: 27" W x 31 5/8" D x 78 5/16" H without casters; 83 5/16" H with casters Auto defrost 115V, 60 Hz, 7.6 Amps, 1/3 HP UL/C-UL listed Shipping weight: 345 lbs.</p>