Product Name: A	ABT-HC-LS-12
· () () () () () () () () () () () () ()	Standard Glass Door Laboratory Refrigerator 12 Cu. Ft. Capacity One swing glass door, self-closing (energy efficient, double pane vacuum insulated), right hinged Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms 2 probes; 1 in air and 1 in sample bottle Remote alarm contacts Adjustable operating temperature: 1°C to 10°C Three adjustable shelves (adjustable in ½" increments) Forced draft air circulation Keyed door lock Magnetic door gasket for positive seal Heavy duty door handle Swivel casters (3 ½") LED interior lights are safety shielded and switch controlled Probe access port (3/8") Powder coated steel white interior and exterior High density urethane foam cabinet insulation Hydrocarbon, natural refrigerant (R290) One year parts and labor warranty, plus an additional four year compressor parts warranty Exterior dimensions: 25" W x 29 ¾" D x 65 ¾" H with casters; 62 ¼" H without casters Cycle defrost 115V, 60 Hz, 3 Amps, 1/5 HP ETL listed Shipping weight: 258 lbs.
· () () () () () () () () () (One swing glass door, self-closing (energy efficient, double pan vacuum insulated), right hinged Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms 2 probes; 1 in air and 1 in sample bottle Remote alarm contacts Adjustable operating temperature: 1°C to 10°C Three adjustable shelves (adjustable in ½" increments) Forced draft air circulation Keyed door lock Magnetic door gasket for positive seal Heavy duty door handle Swivel casters (3 ½") LED interior lights are safety shielded and switch controlled Probe access port (3/8") Powder coated steel white interior and exterior High density urethane foam cabinet insulation Hydrocarbon, natural refrigerant (R290) One year parts and labor warranty, plus an additional four year compressor parts warranty Exterior dimensions: 25" W x 29 ¾" D x 65 ¾" H with casters; 62 H without casters Cycle defrost 115V, 60 Hz, 3 Amps, 1/5 HP