

TRENTO INSERT



LED light



IN/OUT Backlit Knob

Trento provides professional grade performance, while being discreetly mounted inside the cabinetry.

It is available with a 1200 CFM blower for extraordinary ventilating power. Plus the All-In-One design avoids the need to purchase a stainless liner. Hidden metallic in/out knob controls operate the 4-speed blower and LED lighting.

A cleaner kitchen is ensured by Elica's patented angled baffle filters, which capture a higher percentage of contaminants and hold larger volumes of grease than traditional baffle filters.

ELICA PRO SERIES

Dimensions | Models 34 1/2" W x 18" D x 11 1/2" H | ETR134SS TRENTO 34"



















FF ATURES

| Size (in) & Type | 34" wide Insert Chimney |
|-------------------|---|
| Finish | Stainless Steel |
| Controls | IN/OUT Backlit Knob |
| Illumination | 2 LED 7.5 watts LED light, replaceable lamps (1 intensity) |
| Installation Type | Ducted Only |
| Blower Type | Speed 1, 380 CFMs Speed 2, 660 CFMs Speed 3, 950 CFMs Speed 4, 1200 CFMs |
| Filter Type | 2 Dishwasher-Safe, Professional Stainless Steel, Angled Baffle Filters |
| Noise (sones): | Min: 2.05, Max: 7.5 Sones |
| Duct Transition | 10" Round with Back Draft Damper (top only) |
| Electrical | 120 Volts, 60 Hertz |
| | |

Line Drawing

| | Models |
|---|--|
| | ETR134SS* |
| Α | 34" (86.4 cm) |
| В | 18" (45.7 cm) |
| C | 5 ½ (13.8 cm) |
| D | 6 ½" (16.4 cm) |
| E | 27 ⁹ / ₁₆ " (70 cm) |
| F | 12 ⁷ / ₁₆ " (31.6 cm) |
| G | 29 ¹³ / ₁₆ " (75.7 cm) |
| Н | 10 ¹ / ₈ " (25.7 cm) |
| ı | 10" (25.4 cm) |
| J | ³/4" (1.9 cm) |

PLUS



HUSH SYSTEM

An exclusive sound deadening technology that effectively reduces sound levels by over 35%, compared to typical range hoods.



LED LIGHT

LED lighting is undoubtedly the smartest solution in terms of energy saving. Expected life time of over 20.000 hours, represents the most remarkable advantage of LED light bulbs.



PROFESSIONAL PERFORMANCE

Special features and very high performances for models with aspiration capacity between 600 and 1200 CFM's, and noise level between 65 and 75 db(A) at maximum speed. The ideal complement of PRO ranges.



HEAT GUARD

A safety feature that protects the hood and cabinetry from excessive heat, by sensing extreme temperatures (>158 degrees) and will automatically adjusts the blower speed to HIGH. Blower speed will automatically adjust back once temperatures drop to a safe level.



