



Project name:	
Location:	
Item:	Qty:
Model:	



**F-22**

**HIGH-TEMP DOOR TYPE DISHWASHER**



2016-10

## PERFORMANCE FEATURES

- Built-in booster for superior sanitation
- Fully automatic hood-type single rack dishmachine
- Program features wash phase at 150°F (65°C) and final rinse phase at 185°F (85°C)
- Capacity of 45 racks per hour
- Built-in automatic detergent pump for consistent results
- Built-in rinse-additive pump for sparkling results
- Wash dishes and trays with a maximum height of 18.5" (47cm)

## CONSTRUCTION FEATURES

- Body, external housing, wash tank, and all chassis components in brushed stainless steel 304 16 ga.
- Upper and lower wash and rinse jets revolving arms constructed of stainless steel; easy to remove and clean without the need for tools
- Intergrated AISI 18/10 stainless steel booster
- Adjustable bullet-style feet
- Safety two-way automatic micro-switch on the door controlling the operation of the wash motor-pump
- Independently-operated heating elements alternating between booster and wash tank
- Alternating heating resistors reducing maximum absorption thereby reducing energy costs
- Automatic fill and water level regulation of the wash tank
- Wash pump protected with double scrap filters easy to remove for quick cleaning and proper maintenance
- Additional scrap filter provided to protect wash motor pump
- Machine can be installed either as an in-line or corner application with simple field modification
- Side mounted control panel with easy access for service
- Slide out intergrated front control panel provides easy access for service
- Individual digital gauges for both wash and rinse temperatures
- Standard equipment includes: One open combination rack and one peg dish rack 19.75" x 19.75" (500 mm x 500 mm)

## OPTIONAL ACCESSORIES

- Pressure reducing valve (PRV) kit
- Splash shield for corner installations
- Drain water tempering kit



### MVP GROUP CORP.

5659 Royalmount Ave., Montreal, Qc, Canada H4P 2P9

TEL: (514) 737-9701 - TOLL FREE: (888) 275-4538

FAX: (514) 342-3854 - TOLL FREE FAX: (877) 453-8832

[www.mvpgroupcorp.com](http://www.mvpgroupcorp.com) - [sales@mvpgroupcorp.com](mailto:sales@mvpgroupcorp.com)

JET-TECH is a registered trade mark of MVP Group.  
Specifications subject to change without notice.

WARRANTY: 1 year parts and labor. Certain conditions apply. See Owner's Manual for details.

## TECHNICAL FEATURES

- **Rack capacity:** 19.75" x 19.75" (500 mm x 500 mm)
- **Complete operating cycle:** 75 seconds wash and 15 second rinse
- **Wash tank capacity:** 4.75 U.S. gallons (18 litres)
- **Wash tank element:** 4000 watts
- **Wash temperature:** 150°F (65°C)
- **Booster capacity:** 2.7 U.S. gallon (10.2 litres)
- **Booster element:** 9000 watts
- **Booster (water) temperature:** 185°F - 194°F (85°C - 90°C)
- **Maximum power absorption:** 9700 watts
- **Power supply :** 208-240/60
- **Amperage:** Single phase - 46.8 amps or three phase - 27.0 amps (please specify when ordering)
- **Motor-pump:** 1.25 HP with thermic drill to 320°F (160°C) and motor insulation
- **Water consumption:** 1 U.S. gallon per cycle (3.8 litres)
- **Water consumption per hour:** 44.75 U.S. gallons (170.0 litres max.)
- **Water supply:** 1/2" hot water supply 140°F / 60°C
- **Recommended pressure:** 30 p.s.i. (dynamic) (PRV may be required)
- **Water inlet connection:** 3/4" male hose connector (hose included)
- **Drain connection:** 1.5" ID (38mm) hose connection (hose included)
- **Shipping weight:** 342 lbs (155 kg)

