

### TECHNICAL DATA SHEET FOR E32T5 DOUBLE STACKED

Full Size Electric Convection Oven TOUCH SCREEN CONTROL  
Double Stacked on a Stainless Steel Base Stand

E32T5/2 - Double stack with adjustable feet base stand  
E32T5/2C - Double stack with castor base stand

#### DOUBLE STACK FEATURES

- Two 5 full size sheet pan capacity ovens
- Compact 28 $\frac{7}{8}$ " / 735mm width
- Full stainless steel base stand
- Full stainless steel oven spacer frame
- Adjustable feet or castor models
- Guard rail for bottom oven

#### STANDARD FEATURES

- 3 $\frac{1}{3}$ " / 85mm tray spacing
- Touch Screen control
- Program and manual modes
- Icon driven program menu
- Up to 5 cooking stages
- Individual shelf timers
- USB port for program/icon updating
- Moisture injection mode (5 levels)
- 2 speed bi-directional reversing fan system
- 6.3kW heating (220-240V) / 5.6kW heating (208V)
- Safe-Touch vented side hinged door (standard LH hinge).  
Optional RH hinge (field convertible)
- Stay-Cool door handle
- Porcelain enameled oven chamber
- Plug-in continuous oven door seal
- Dual halogen oven lamps
- Anti-skid 2" / 50mm dia. 3" / 76mm high adjustable stainless steel feet
- 100% recyclable packaging

#### ACCESSORIES

- Optional M236060 Core Temperature Probe Kit



**THE ADVANTAGE**

Model E32T5/2C shown

#### E32T5/2 E32T5/2C

Units shall be a Moffat electrically heated Turbofan convection ovens E.T.L. listed and NSF-4 listed. The ovens shall have a one piece porcelain enameled oven chamber, stainless exterior top and sides. The oven shall have a vented safe touch side hinged door that offers field reversible hinging. Oven shall have capacity for 5 full size sheet pans. The ovens shall have selectable moisture level injection and a 2 speed oven fan. The ovens shall be controlled by a 5.7" Touch Screen control with manual and recipe operating modes with icon driven recipe programs and individual shelf control operation mode and multiple stage cooking. Ovens controller shall have USB port for recipe file uploading and downloading. A core temperature probe M236060 is optional. The ovens shall include dual halogen oven lamps. Ovens shall be double stacked using Double Stacking Kits DSK32 (adjustable feet option) or DSK32C (castor option). Units shall be supplied in 100% recyclable shipping packaging.

Double stack models are supplied as two individual ovens and a double stacking kit for field assembly.

# 30T SERIES

E32T5/2  
E32T5/2C

# turbofan®

## E32T5/2 E32T5/2C Full Size Convection Oven TOUCH SCREEN CONTROL Double Stacked on a Stainless Steel Base Stand

### CONSTRUCTION

Porcelain enameled fully welded oven chamber  
Stainless steel front, sides and top exterior  
Stainless steel oven fan baffle and oven vent  
Removable 5 position stainless steel side racks  
Oven racks chrome plated wire (5 supplied)  
Stainless steel frame side hinged door  
0.2" / 5mm thick door outer glass  
0.2" / 5mm thick low energy loss door inner glass  
Full stainless steel welded door handle  
Stainless steel control panel  
Aluminized coated steel base and rear panels

### CONSTRUCTION - DOUBLE STACKING KIT

All stainless steel construction  
Welded 1½" and 1¼" square tube front and rear frame  
base stand  
4 adjustable feet on E32T5/2  
4 dia. 3" / 76mm swivel castors with 2 front castors dual  
wheel and swivel lock on E32T5/2C  
Stainless steel oven spacer frame  
Stainless steel bottom oven vent extension

### CONTROLS (each oven)

5.7" LED backlit touch screen  
Icon driven program menu  
BMP image icon imports via USB port  
Program updates via USB port  
Temperature range 85-500°F  
Adjustable sounder tones and volume  
Other specification on request  
Safety thermostat cut-out  
Optional core temp probe

### CLEANING

Stainless steel top and side exterior panels  
Porcelain enameled oven chamber  
Fully removable stainless steel oven side racks  
Removable stainless steel oven fan baffle  
Easy clean door system with hinge out door inner glass (no  
tools required)  
Removable plug-in oven door seal (no tools required)

### SPECIFICATIONS

Electrical Requirements (each oven)  
208V, 60Hz, 1-phase, 5.8kW, 28A  
220-240V, 60Hz, 1-phase, 6.5W, 27A  
No cordset supplied

### Water Requirements (optional - each oven)

Cold water connection ¾" GHT male  
80psi maximum inlet pressure / 20psi minimum inlet pressure

### External Dimensions

Width 28½" / 735mm  
Height 67¾" / 1720mm  
Depth 33¾" / 858mm

### Oven Internal Dimensions (each oven)

Width 18¼" / 465mm  
Height 20¼" / 515mm  
Depth 27½" / 700mm  
Volume 6ft³ / 0.17m³

### Oven Rack Dimensions

Width 18" / 460mm  
Depth 26" / 660mm

### Nett Weight (double stack complete)

470lbs / 213kg

### Packing Data (E32T5 ovens each)

231lbs / 105kg  
20.1ft³ / 0.57m³  
Width 29½" / 760mm  
Height 32" / 815mm  
Depth 36¾" / 925mm

### Packing Data (Stacking Kit)

35lbs / 16kg (DSKE32 - adjustable feet)  
41lbs / 19kg (DSKE32C - castor)  
4.1ft³ / 0.12m³  
Width 30¾" / 770mm  
Height 35" / 890mm  
Depth 6¾" / 170mm

Supplied CKD for assembly on site

### INSTALLATION CLEARANCES

Rear 2" / 50mm  
LH Side 2" / 50mm  
RH Side\* 3" / 75mm

\* For fixed installations a minimum of 20" / 500mm is required for service

### CLEARANCE FROM SOURCES OF HEAT

A minimum distance of 12" / 300mm from the appliance sides is required

### Double Stacking Kits

For after market double stacking two E32T5 convection ovens  
DSKE32 - Double stacking kit - adjustable feet  
DSKE32C - Double stacking kit - castor

**MOFFAT®**

www.moffat.com

U.S.A.

Moffat Inc

3765 Champion Boulevard

Winston-Salem

North Carolina 27105

Ph Toll Free 1-800-551 8795

Ph 336-661 0257

Fax 336-661 9546

Email sales@moffat.com

www.moffat.com

Manufactured by:

Moffat Limited

16 Osborne Street PO Box 10-001

Christchurch 8081 New Zealand



**ISO9001**  
Quality  
Management  
Standard

Designed and manufactured by

**MOFFAT®**

ISO9001

All Turbofan products are designed and manufactured by Moffat using the internationally recognised ISO9001 quality management system, covering design, manufacture and final inspection, ensuring consistent high quality at all times.

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

© Copyright Moffat Ltd  
Moffat 1318 / 1.13

