

SEDONA BY LYNX™ SERIES

30'' SEDONA BUILT-IN GRILL WITH ROTISSERIE, 1 PROSEAR INFRARED BURNER AND 1 STAINLESS STEEL BURNER (L500PSR)







L500PSR PRODUCT OVERVIEW

- Precise power—one ProSear™ Infrared Burner and one Stainless Steel Burner combining to provide up to 46,000 BTU
- Consistent assurance—direct spark ignition with battery backup
- Perfect clarity—dual halogen grill surface lights
- Quick visibility—temperature gauge
- Easy opening—Lynx Hood Assist
- Ready rotisserie—dedicated rotisserie back burner, motor, spit rods, and forks
- Ample capacity—733 square inches of cooking surface (508 primary, 225 secondary)
- Beautiful illumination—blue-lit control knobs
- Steady performance—heat-stabilizing design
- Smooth opening—fluid rotation handle
- Premier platform—stainless steel grilling grates
- Steadfast durability—heavy-duty welded construction eliminates gaps where grease can collect





L500PSR PRODUCT FEATURES

The Sedona by Lynx[™] Series is always evolving to be the best at something new. That philosophy is reflected in its features. We've refined these features to give you a grilling experience that's both simple and stunning.

STAINLESS STEEL BURNERS

SPARK IGNITION SYSTEM

FOR MORE **INFORMATION ON** SEDONA BY LYNX™ SERIES **PRODUCT FEATURES**, PLEASE VISIT

LYNXGRILLS.COM



PROSEAR™ INFRARED BURNER



EXPANSIVE GRILLING SURFACE



ROTISSERIE SYSTEM



CUT-OUT DIMENSIONS: WIDTH: 29" / HEIGHT: 10" / DEPTH: 21.25"

SHIPPING DIMENSIONS: WIDTH 35" / HEIGHT 33.5" / DEPTH 30" SHIPPING WEIGHT: 168 POUNDS



GAS REQUIREMENTS: SHIPS IN LIQUID PROPANE OR NATURAL GAS FROM FACTORY



PRODUCT TECHNICAL SPECIFICATIONS

ELECTRICAL REQUIREMENTS: INSTALLATION REQUIRES AN OUTDOOR 120V/15GFI ELECTRICAL OUTLET ADJACENT TO PRODUCT



COOKING CONFIGURATION: BUILT-IN GRILL WITH ROTISSERIE, 1 PROSEAR **INFRARED BURNER AND 1 STAINLESS STEEL BURNER**



CERAMIC RADIANT BRIQUETTES



LYNX HOOD ASSIST





SEAMLESS WELDED CONSTRUCTION



INTEGRATED ILLUMINATION


L500 ISLAND PREPARATION






COUNTERTOP NOTCH DETAIL

INSULATING JACKET





Note: Insulating jacket required for all grills installed into a combustible enclosure. For natural gas grills, mmends using ¾" gas lines. Side burners may be rotated 90 degrees. See installation manuals for details.

IDLYNX FOR EVEN MORE ON THIS PRODUCT AND OTHER COMPLIMENTARY LYNX PRODUCTS, VISIT LYNXGRILLS.COM