

SCFM162



33.25" x 53.75" x 28.63" (H x W x D)

Commercially listed 14.1 cu.ft. manual defrost chest freezer

Highlights:

Commercially approved for use in foodservice establishments

Hammered aluminum interior offers added durability for long-lasting use

Manual defrost operation and static cooling system

Product Features:

Commercially approved	UL-S listed to ANSI-NSF Standard 7 for commercial use
Manual defrost operation	Static cooling system
Hammered aluminum interior	Solid construction for lasting durability
Adjustable thermostat	Dial thermostat for easy temperature management
Storage baskets	Two removable plastic baskets offer convenient storage
Stainless steel front corner protectors	External "bumpers" are factory installed to protect the unit's front corners from dents
White exterior	Textured white finish fits well in any establishment
100% CFC free	Environmentally friendly design without ozone-damaging chemicals
CARB Compliant	Environmentally friendly hydrocarbon-based refrigerant for a greener footprint that meets current CARB regulations



SCFM162 Specifications:

Overview

Height of Cabinet	33.25" (84 cm)
Width	53.75" (137 cm)
Depth	28.63" (73 cm)
Capacity	14.1 cu.ft. (399 L)
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Sanitation	UL-S
Amps	1.49
Voltage/Frequency	115 V AC/60 Hz
Weight	130.0 lbs. (59 kg)
Shipping Weight	140.0 lbs. (64 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101052120
Freezer	
Door Swing	Lift-Up
Interior Height	26.25" (67 cm)
Interior Width	48.0" (122 cm)
Interior Depth	21.5" (55 cm)
Thermostat Type	Dial
Refrigerant Type	R600a
Refrigerant Amount	3.53 oz.
High Side PSI	150.0
Low Side PSI	54.0
Wheels	4
Compressor Step Height	9.25" (23 cm)
Compressor Step Width	9.38" (24 cm)
Compressor Step Depth	21.5" (55 cm)
Temperature Range	-30 to -12°C/-22 to 10.4°F

