more durable, efficient, beautiful	4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com	Project :	
		Model # :	
		Item # :	Qty :
		Available W/H :	
		Approval :	

Glass Door Undercounter Ref.

Side Mount Undercounters J Series

Model : JUR-60-G-N



____ FEATURES & BENEFITS ____

 Digital temperature control & monitor system Keep food products safe by maintaining constant temperatures. External digital display allows for easy monitoring.

Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet the new standards of the EPA and DOE in 2017. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

Side mount compressor unit

With compressors positioned on the side of the unit, our refrigerators can now be serviced without being moved. Our innovative, front breathing feature also allows this model to be highly efficient in narrow spaces.

Exterior & interior of the cabinet

The Turbo Air J series boasts a stainless steel exterior with glass doors & AL frame (galvanized steel back and bottom). Interior is stainless steel floor with AL sides and back. It guarantees the utmost in cleanliness and long product life. The J series adds a touch of style to the most refined setting.

Hot gas condensate system

Through Turbo Air's creative innovation, the condensate system surfaces have been specially treated to resist corrosion. This not only increases efficiency without the risk of refrigerant leakage from corrosion, but also thoroughly prevents the overflow of condensate water.

LED interior lighting & fan control

- High-density polyurethane insulation The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.
- Ergonomically designed doors Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience.

Magnetic door gaskets

Magnetic door gaskets are of one-piece construction, removable without tools for ease of cleaning and replacement.

- Adjustable, heavy duty, PE (polyethylene) coated wire shelves
- Easy open front grille with condenser cleaning brush kit

Front grille cover is easily removable without any tools, which makes condenser cleaning easy and convenient at any time. Handy condenser cleaning brush is included inside the front grille cover.

Refrigerator holds 33°F ~ 39°F for the best in food preservation

						Refrig	erant 🦳 🛁	tertek Intertek
	Model	Swing Door	CU./FT.	#of Shelves	HP	AMPS	Crated Weight (lbs.)	$L \ge D^* \ge H^+$ (inches)
	JUR-60-G-N	2	13.58	2	1/3	2.3	275	59 x 271/2 x 283/4

Ver.20171010

* Depth does not include 1" for rear spacers. † Height does not include 5" for caster height.

Glass Door Undercounter Ref.

Model: JUR-60-G-N

ELECTRICAL DATA					
Voltage	115/60/1				
Plug Type	NEMA 5-15P				
Full Load Amperes	2.3				
Compressor HP	1/3				
Cord Length (ft.)	9.2				
Refrigerant	R-290				
DIMENSIONAL DATA					
Net Capacity (cu. ft.)	13.58				
Ext. Length Overall (in.)	59 (1499mm)				
Ext. Depth Overall (in.)*	271/2 (699mm)				
Ext. Height Overall (in.) [†]	283/4 (730mm)				
# of Doors	2				
# of Shelves	2				
Net Weight (lbs.)	205				
Gross Weight (lbs.)	275				
Shelf Size (in.)	20 1/4 x 21 1/2				

Design and specifications subject to change without notice. Actual shipping weight may differ due to extra packing materials for product protection.


* Depth does not include 1" for rear spacers. † Height does not include 5" for caster height.

2 Year Parts and Labor Warranty Additional 3 Year Warranty on Compressor **WARRANTY**:

- Anti-corrosion coated evaporator
- Self-contained system
- Standard 4" dia. swivel casters with locks on the front set
- Standard door locks
- 2.5" caster available (optional)
- Legs available for all models (optional)

OPTIONAL ACCESSORIES :


- 2.5" caster, ½" diameter & 13 TPI: 30265H0100 (non-brake), 30265H0200 (w/ brake)
- 5" caster, 1/2" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- G" ABS plastic leg: 30221M0200
- G" stainless steel leg: 30221M0600
- Additional PE coated wire shelf: KR59000100





(H)

(H)



SIDE VIEW

Ver.20171010



- **Turbo Air** : 800-627-0032 **GK** : 800-500-3519
- Warranty : 800-381-7770 AC : 888-900-1002





GREEN WORLD Turbo air