

# **BI1215SOD** • 15" Outdoor Crescent Ice Maker • Outdoor Series





STAINLESS SOLID

# **FEATURES & BENEFITS**

# PERFORMANCE

- Uses less than 3 gallons of water to produce up to 25 lbs of ice per day
- Up to 25 lbs in ice storage capacity
- Daily ice production rate is approx. 4 times greater than the average household refrigerator
- Crescent ice cube dimensions: 1/2" W x 3/4" H x 2 1/4" L
- On/Off switch is conveniently located on lower face of unit

# INTERIOR/EXTERIOR

### • No drain required

- Standard professional stainless steel handle is interchangeable with commercial handle accessory
- Full stainless steel cabinet and door are deemed suitable for outdoor use by UL
- Door swing is field reversible, and is shipped right-hand hinged

# INTEGRATION

- Unit is designed to be built-in or can be freestanding
- Four independently adjustable leveling legs provide a precise undercounter fit

# MODEL DETAILS

Model	Voltage/Hz	Door Swing	Finish	Shipping Weight
U-BI1215SOD-00B	115 / 60	Field Reversible	Stainless Solid	89 lb


### **ACCESSORIES**

Model	Description	Finish	Shipping Weight
80-54214-00	Commercial Door Handle, 7/8" Diameter	Stainless	2 lb



# Outdoor Series • 15" Outdoor Crescent Ice Maker • BI1215SOD


### **DIMENSIONS**



### **SPECIFICATIONS**

Model	BI1215SOD	
Amps: Running	2.5	
Control Type	On/Off Switch	
Defrost Type	Manual	
Dimensions: Depth	23 ½" / 591 mm	
Dimensions: Height	34 ½" / 867 mm	
Dimensions: Width	14 <sup>15</sup> / <sub>16</sub> " / 379 mm	
ENERGY STAR	N/A	
Ice Production Per Day	25 lb	
Ice Storage	25 lb	
Product Weight: Max	83 lb	
Refrigerant Type	R134a	
Sabbath (Star K Certified)	No	

### **CABINET CUT-OUT**



### **INSTALLATION NOTES**

When installing adjacent to wall, ensure 2-1/2" clearance on hinged side for 90° door opening, allowing ample room for door handle.

No additional clearance around sides, top or rear of unit is needed for ventilation.

Do not obstruct front grille air flow.

# **ELECTRICAL REQUIREMENTS**

This unit requires a grounded, polarized 115 VAC, 60 Hz, 15 A power supply (normal household current).





Warranty

Deemed suitable for outdoor use by UL.

Please visit u-line.com to view this model's User Guide & Service Manual. All Specifications are subject to change without notice.