







Stainless Solid

Integrated Solid

Key Features

- Convection cooling system provides a quick cool down and consistent temperature
- Converts to a refrigerator with the touch of a button
- White interior
- Three full-extension chrome plated slide-out baskets
- Stainless steel full-wrap door and handle (1/8" diameter)
- Stainless steel grille (stainless model), black metal grille (integrated model)
- Digital touch pad control

- Refrigerator temperature range: 34°F to 45°F
- Freezer temperature range: -5°F to 5°F
- Bright white LED lighting
- Volume of 4.8 cu ft
- Field reversible door is shipped right-hand hinged
- Integrated model requires 3/4" custom door panel and handle (not supplied by U-Line)
- Built-in or freestanding
- Four adjustable leveling legs

Model Details

Model	Voltage/Hz	Door Swing	Finish	Shipping Weight
UHFZ124-SS01B	115 / 60	Field Reversible	Stainless Solid	125 lb
UHFZ124-IS01B	115 / 60	Field Reversible	Integrated Solid	122 lb

Accessories


Model		Description	Finish	Shipping Weight
	ULAFREESTANDB	Freestanding Kit	Black	3 lb

Front Side Top 22 1/2" 23 15/16" 24 3/8 (608 mm) (613 mm) 20 %" (530 mm) 7 %" (200 mm) 34 %" to 35 %" 28" (867 mm to (711 mm) 14 %" 892 mm) (371 mm) 6 %" (162 mm) 24 ½" (622mm) (210 mm) (91 mm) 1" (25 mm)


Specifications

Model	HFZ124
Amps: Running (115 v)	2.5 A
Capacity: Total Volume (cu ft)	4.8 cu ft
Dimensions: Product Depth	22 ½" / 572 mm
Dimensions: Product Height	34 ½" / 867 mm
Dimensions: Product Width	23 ¹⁵ / ₁₆ " / 608 mm
ENERGY STAR	Tier 1
Energy Consumption: Avg. Per Year	390 kWh
Panel Height	30 ¹ / ₄ " / 768 mm
Panel Thickness	3/4" / 20 mm
Panel Type	Solid Panel
Panel Width	23 ³ / ₄ " / 603 mm
Refrigerant Type	R600a (1.23 oz)
Sabbath (Star K Certified)	Yes
Temperature Range	-5°F to 5°F / 34°F to 45°F

Back



Cabinet Cut-Out



Warranty

- 1 Year (parts & labor) / 5 year sealed system (parts)
- + Additional 1 Year (parts & labor) warranty at no cost with product registration

See complete warranty for details



Installation Notes

- 24" cutout width sufficient if door protrudes beyond adjacent cabinetry
- No additional clearance is needed for ventilation
- Do not obstruct front grille air flow









