

**No Lead Floor Model Water Cooler  
Sensor-Operated Air Cooled  
Model EFOA8**



**SPECIFICATIONS**

**GENERAL**

Model EFOA8 has the Flexi-Guard® Safety Bubbler with an electronic sensor-operated valve and automatic flow regulator to provide constant stream from 20 to 105 psi. Bubbler orifice is fully protected to meet all sanitary codes.

Non-pressurized tank system is standard. Non-pressurized water tank is located after solenoid valve, so that tank is subject to line pressure only when sensor is activated.

**NO LEAD DESIGN**

**THIS WATER COOLER COMPLIES WITH THE LEAD-FREE DEFINITION IN THE SAFE DRINKING WATER ACT OF 1986 AND LEAD CONTAMINATION CONTROL ACT OF 1988.**

Elkay Water Coolers are manufactured with a waterway system utilizing copper components and completely lead-free materials. These waterways have no lead because all lead materials, such as leaded brass, have been removed. All joints are brazed using silver solder only. No lead solder is permitted. A strainer with an easily cleanable screen is provided to allow trapping and convenient removal of water born particulate of 140 microns and larger prior to their entry into the water cooler.



This water cooler is classified by Underwriters Laboratories Inc. in accordance with **ANSI/NSF61, Section 9-1997b.**

**CAPACITIES CHART**

Model Number	Base Rate	*GPH of 5 °F Drinking Water					Rated Watts	Full Load Amps	Glass Filler Option	Ship. Wt. Lbs.
		Room Temperature °F								
		7 °F	8 °F	9 °F	1 °F	°F				
EFOA8	5.3	9.2	8.6	8.0	7.4	420	5.5	No	81	

\*Based on 80°F inlet water temperature. Rated watts shown are based on operational (run) time, in accordance with A.R.I. Standard 1010 conditions. Specific applications will determine the actual watts consumed per hour. Watts consumed will be based on number of people served per hour (usage), ambient temperatures, and inlet water temperature.

**COOLING SYSTEM**

**Motor Compressor:** Hermetically sealed, reciprocating type, 115V, 60 Hertz. All are single phase. Sealed in lifetime oil supply. Equipped with electric cord and three prong molded rubber plug.

**Condenser:** Fan cooled, copper tube with aluminum fins. Fan motor is permanently lubricated.

**Cooling Unit:** Combination tube-tank type. Tube portion is continuous coil of copper tubing. Tank is stainless steel. Fully insulated with EPS foam which meets Underwriters Laboratories Inc. requirements for self extinguishing material.


**Refrigerant Control:** Refrigerant HFC-134a is controlled by accurately calibrated capillary tube for positively trouble free performance.

**Temperature Control:** Enclosed adjustable thermostat is factory preset. Requires no adjustment other than for altitude requirements.

**CONSTRUCTION**

**Fountain Top:** Type 304 one piece stainless steel top, polished to a uniform Elkay bright luster finish. Exclusive Cascade basin, tested most splash resistant, features multi-level deck design with a built-in vandal-resistant strainer.

**Electronic Sensor Operation:** On-Off solenoid valve is actuated by an infra-red lightbeam sensor. When lightbeam is interrupted by subject in front of cooler desiring a drink, the



Model EFOA8

sensor actuates the solenoid valve which then opens to allow water flow. No physical contact with cooler is required. A built in time delay is provided to prevent actuation by persons moving past cooler. There is a maximum running time of 30 seconds to prevent malicious damage to the cooler or water damage if sensor vision is blocked. Unit automatically resets when blockage is removed.

**Exclusive Flexi-Guard® Safety Bubbler\*\*:** Innovative design utilizes a pliable elastomer to prevent accidental mouth injuries. Flexes on impact, then returns to original position. Strong. Abrasion-resistant. Anti-sweat.

**Removable Panel:** Removable front panel offers easy accessibility to interior.

**Color Selection:** Gray Beige vinyl furnished as standard unless alternate panel color is selected. Alternate panel colors in vinyl are: Granite, Sandalwood and Natural Almond. All furnished at no extra cost. Stainless Steel available at extra cost.

**Cabinet:** Cabinet design allows for flush to wall mounting, or free standing.

**5 YEAR LIMITED WARRANTY** on the refrigeration system of the unit. Electrical components and water system are warranted for 12 months from date of installation. Sample Certificate available on request.

Elkay Pressure-Type Water Coolers are designed to operate on 20 psi to 105 psi supply line pressure. If inlet pressure is above 105 psi, a pressure regulator must be installed in the supply line. Any damage caused by reason of connecting this product to supply line pressures lower than 20 psi or higher than 105 psi is not covered by the warranty.

**Note:** In keeping with our policy of continuing product improvement, Elkay reserves the right to change materials, design and specifications without notice.

Elkay Electric Air Cooled Water Coolers are listed by Underwriters Laboratories Inc., approved by C.S.A., rated in accordance with A.R.I. Standard 1010 and meet all known federal and state plumbing codes.




\*\* Patent #4,481,971


**No Lead Floor Model Water Cooler  
Sensor-Operated Air Cooled  
Model EFOA8**



**ROUGH-IN DIMENSIONS**



**OPERATION OF QUICK CONNECT FITTINGS**




PUSHING TUBE IN BEFORE PULLING IT OUT HELPS TO RELEASE TUBE

**IMPORTANT!  
INSTALLER PLEASE NOTE:**

This water cooler has been designed and built to provide water to the user which has not been altered by materials in the cooler waterways. The grounding of electrical equipment such as telephone, computers, etc., to water lines is a common procedure. This grounding may be in the building but may also occur away from the building. This grounding can cause electrical feedback into a water cooler creating an electrolysis which creates a metallic taste or causes an increase in the metal content of the water. This condition is avoidable by installing the cooler using the proper materials as shown below.

**NOTICE**

This water cooler must be connected to the water supply using a dielectric coupling. The cooler is furnished with a non-metallic strainer which meets this requirement. The drain trap which is provided by the installer should also be plastic to completely isolate the cooler from the building plumbing system.



**PLUMBING ROUGH-IN CAN BE LOCATED ANYWHERE WITHIN THIS AREA.**