



CONTROL CENTER MODEL MRS

SPECIFICATIONS


- 3 - Button switch with FWD/STOP/REV
- Stainless steel construction
- NEMA 4 - water tight enclosure
- Manual reverse allows increased cutting element life and reduces jams
- Magnetic starter/provides automatic shut-off in case of power interruption
- Operates on line voltage

VOLTAGE/PHASE AVAILABILITY

Model	Voltage/Hz	Phase
MRS-6	120V, 50/60 Hz	1 Ph
MRS-7	208-240V, 50/60 Hz	1 Ph
MRS-8	208-240V, 50/60 Hz	3 Ph
MRS-9	380-460V, 50/60 Hz	3 Ph




RECOMMENDED INSTALLATION



NOTE: The MRS control center should be mounted 1-1/2" (38.1 mm) back from the front surface of the table.

DIMENSIONS



A complete collection of our product drawings is available for download at the **InSinkErator Revit/CAD Library**, which can be found at www.insinkerator.com/foodservice. Product information is also accessible on **The KCL CADalog**. More information is available from KCL at www.kclcad.com.



4700 21st STREET
 RACINE, WI 53406
 TEL: 800-845-8345
 FAX: 262 554-3620
www.insinkerator.com/foodservice



The Emerson logo is a trademark and a service mark of Emerson Electric Co.

