KOHLER® **Roughing-In**

K-1110-AH **PURIST**® **BATH WHIRLPOOL WITH SPA EXPERIENCE**

Product Information

Applicable product:						
Bath whirlp	bool with S	pa Experience		K-	1110-AH	
				1		
Fixture*:						
Bathing we	ell:					
Basin area, bottom		45" (114.3 cm) x 25-1/2" (64.8 cm)				
Basin area, top		63" (160 cm) x 31-1/2" (80 cm)				
Weight		160 lbs (72.6 kg)				
To overflow	v:					
Water depth to rim		21" (53.3 cm)				
Capacity		115 gal (435.3 L)				
* Approximate measurements for comparison only.						
					-	
Included c	omponents	:				
Cut-out ter				1016369-7		
Pump	Heater	V	Hz		A	
	1.5 kW	240	50/	60	11	

Required accessories: Template kit (undermount only) K-589 Clearflo horizontal overflow bath drain K-7273

Required Electrical Service

Dedicated circuit required, pr Ground-Fault Circuit-Interrup Current Device (RCD):	ter (GFCI) or Residual
Pump/control	220/240 V, 20 A, 50/60 Hz

Installation Notes

Install this product according to the installation guide.

Pump/piping protrudes beyond rim (see below).

Floor support under whirlpool must provide a minimum of 50 lbs/square foot (243 kg/square meter) loading.

Hot water supply should be 70% of capacity or greater. Installations will vary.

Fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

12-3/16"

3-15/16"

No change in measurements with drain shown. (K-7273)

