

Product Information

| | |
|---|------------|
| Applicable product: | |
| 5' Bubblemassage bath – integral apron, left drain | K-1151-GLA |
| 5' Bubblemassage bath – integral apron, right drain (shown) | K-1151-GRA |

| | |
|---|--------------------------------|
| Fixture*: | |
| Bathing well: | |
| Basin area, bottom | 45" (114.3 cm) x 22" (55.9 cm) |
| Basin area, top | 54" (137.2 cm) x 25" (63.5 cm) |
| Weight | 100 lbs (45.4 kg) |
| To overflow: | |
| Water depth | 15" (38.1 cm) |
| Capacity | 60 gal (227.1 L) |
| * Approximate measurements for comparison only. | |

| | | | | |
|---------------|--------|-----|----|---|
| Blower motor: | Heater | V | Hz | A |
| | 300 W | 120 | 60 | 5 |

Required Electrical Service

| | |
|---|--------------------|
| Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI): | |
| Blower motor | 120 V, 15 A, 60 Hz |
| Blower motor is supplied with a 24" (61 cm) grounding-type plug-in cord. | |

Installation Notes

NOTICE: If the blower motor and check valve are relocated, the following two procedures are required: 1. Provide two access panels. Locate one access panel at the blower motor/control location and the other access panel at the control box. **2.** Relocate the blower motor and the check valve together. Do not relocate one without the other.

Install this product according to the installation guide.

Floor support under the bath must provide for a minimum of 49 lbs/square foot (238 kg/square meter) loading.

Fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

No change in measurements if connected with drain illustrated. (K-11677)

