

Product Information

Applicable products:	
Bath whirlpool with integral apron and heater – left drain	K-1109-HL
Bath whirlpool with integral apron and heater – right drain	K-1109-HR

Fixture*:	
Basin area:	
Bathing well	42" (106.7 cm) x 20" (50.8 cm)
Top area	51" (129.5 cm) x 24" (61 cm)
Weight	135 lbs (61.2 kg)
To overflow:	
Water depth	14" (35.6 cm)
Capacity	60 gal (227.1 L)
* Approximate measurements for comparison only.	

Pump:	V	Hz	A
1-speed	120	60	7
Heater:	kW	V	Hz
	1.5	120	60
			A
			12.5

Required Electrical Service

Two dedicated circuits required, each protected with Class A Ground-Fault Circuit-Interrupter (GFCI):	
Pump/control	120 V, 15 A, 60 Hz
Heater	120 V, 15 A, 60 Hz
Locate the outlets behind the whirlpool and within 24" (61 cm) of the pump.	

Installation Notes

Install this product according to the installation guide.
 Floor support under whirlpool must provide for a minimum of 50 lbs/square foot (242 kg/square meter) loading.
 Fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

No change in measurements if connected with drain illustrated. (K-7161-AF or K-7161M-AF)

