

# KOHLER®

## Roughing-In

## K-1457-G, K-1457-GCR PORTRAIT® 5.5' BUBBLEMASSAGE™ BATH WITH AIRJETS

### Product Information

Applicable products:				
BubbleMassage bath with airjets	K-1457-G			
BubbleMassage bath with airjets and chromatherapy	K-1457-GCR			
Fixture*:				
Basin area:				
Bathing well, bottom	50" (127 cm) x 29" (73.7 cm)			
Bathing well, top	61" (154.9 cm) x 32" (81.3 cm)			
Weight	128 lbs (58.1 kg)			
To overflow:				
Water depth	16" (40.6 cm)			
Capacity	100 gal (378.5 L)			
* Approximate measurements for comparison only.				
Included components:				
Cut-out template	113311-7			
Blower motor / control:	kW	V	Hz	A
	300	220-240	50/60	3

### Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Residual Current Device (RCD):

Blower motor/control	220-240 V, 15 A, 50/60 Hz
----------------------	---------------------------

### Installation Notes

The blower motor and piping protrude beyond the rim.

Install this product according to the installation guide.

Floor support under bath must provide for a minimum of 51 lbs/square foot (246.8 kg/square meter).

Hot water supply should be 70% of capacity or greater. Installations will vary.

If installing a rim mount faucet, make sure there is no interference with drain overflow and circulating system before drilling any holes. Consult local and national codes for minimum air gap requirements if installing a spout on the faucet deck.

This bath is designed for drop-in installation only. It is not suited for use in a three wall alcove with an overhead shower.

A blower motor/control access panel is required.

Fixture dimensions are nominal and conform to tolerances in ANSI Standard Z124.1.2.

No change in measurements with drain shown. (K-7161-AF or K-7161M-AF)

Recommended faucet area.

**Note:** The blower and piping protrude beyond the rim.

