

KOHLER® Roughing-In

K-723-H2, K-724-H2
MEMOIRS®
5' BATH WHIRLPOOL

Product Information

Applicable products:	
5' bath whirlpool – left drain	K-723-H2
5' bath whirlpool – right drain	K-724-H2
ADA compliant when installed per Section 607 of the Act.	ADA

Fixture*:	
Bathing well:	
Basin area, bottom	45" (114.3 cm) x 23" (58.4 cm)
Basin area, top	54" (137.2 cm) x 25" (63.5 cm)
Weight	390 lbs (176.9 kg)
To overflow:	
Water depth	11-5/8" (29.5 cm)
Capacity	52 gal (196.8 L)
* Approximate measurements for comparison only.	

Pump	kW	V	A*
	1.5	240	11
* Approximate measurements for comparison only.			

Minimum access panel (required):	
Pump/control	30" (76.2 cm) W x 15" (38.1 cm) H

Required accessories:	
Jet trim kit	K-9696

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Residual Current Device (RCD):	
Pump/control	208-240 V, 20 A, 50/60 Hz

Installation Notes

NOTE: Pump protrusion beyond rim.
Install this product according to the installation guide.
Floor support under whirlpool must provide for a minimum of 61 lbs/square foot (295 kg/square meter) loading.
Fixtures conforms to ASME Standard A112.19.1. All dimensions are nominal.

No change in measurements if connected with drain illustrated. (K-7161-AF or K-7161M-AF)

Note: Pump Protrudes Beyond Rim

