

KOHLER® Roughing-In

K-865-HB, K-865-HD, K-865-HM
TEA-FOR-TWO®
6' BATH WHIRLPOOL

Product Information

Applicable products:	
6' bath whirlpool, custom pump	K-865-HB
6' bath whirlpool, custom pump	K-865-HD
6' bath whirlpool, custom pump	K-865-HM

Fixture*:	
Bathing well:	
Basin area, bottom	49" (124.5 cm) x 22" (55.9 cm)
Basin area, top	62" (157.5 cm) x 28" (71.1 cm)
Weight	455 lbs (206.4 kg)
To overflow:	
Water depth	17" (43.2 cm)
Capacity	89 gal (336.9 L)
* Approximate measurements for comparison only.	

Pump	kW	V	A*
	1.5	240	11
* Approximate measurements for comparison only.			

Drop-in cut-out	70-1/4" (178.4 cm) x 34-1/2" (87.6 cm)
-----------------	--

Included component:	
Cut-out for undermount	K-582 template

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Residual Current Device (RCD):	
Pump/control	208-240 V, 20 A, 50/60 Hz

Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 69 lbs/square foot (333 kg/square meter) loading.

Cast iron whirlpools are extremely heavy, making some drop-in installations difficult. Splitting the deck/surround is recommended if installing into a deck.

Hot water supply should be 70% of capacity or greater. Installations will vary.

Pump must be relocated to custom position at the time of installation. Provide adequate clearance.

Fixture conforms to ASME Standard A112.19.1. All dimensions are nominal.

