

Product Information

Applicable product:	
5' Curved apron bath with Bask heated surface – left drain	K-1100-LAW
5' Curved apron bath with Bask heated surface – right drain	K-1100-RAW

Fixture*:	
Bathing well:	
Basin area, top	54" (1372 mm) x 31" (787 mm)
Basin area, bottom	45-11/16" (1160 mm) x 27-5/8" (702 mm)
Weight	78 lbs (35.4 kg)
To overflow:	
Water depth	12-5/8" (321 mm)
Capacity	60 gal (227.1 L)
* Approximate measurements for comparison only.	

Heater:	W	V	HZ	A
	65	120	60	1.1

Recommended accessories:	
Clearflo 1-1/2" adjustable pop-up bath drain	K-7161
Clearflo cable bath drain with PVC tubing	K-7213
Clearflo cable bath drain without PVC tubing	K-7214

Installation Notes

Install this product according to the installation guide.

Floor support under bath must provide for minimum of 38 lbs/square foot (186 kg/square meter) loading.

The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary.

Locate a GFCI-protected 120 V, 15 A, grounded electrical outlet within 24" (610 mm) of the bath junction box.

40" (1016 mm) cable is included.

Fixture conforms to CSA B45.5/IAPMO Z124. All dimensions are nominal.

