

Features


- Vitreous china
- Washout
- Rear supply
- Includes removable strainer, 2" outlet spud, universal mounting bracket, hangers, flexible supply hose, and 5/8" adapter
- WaterSense_® compliant when used with WaterSense flushometer
- 0.125 gpf (0.47 lpf)
- 15-5/8" (397 mm) extended rim

Codes/Standards Applicable

- Being developed to meet or exceed the following:
- ICC/ANSI A117.1
- ASME A112.19.2/CSA B45.1
- ADA
- EPA WaterSense_®



ADA



Colors/Finishes

- 0: White
- Other: Refer to Price Book for additional colors/finishes

Accessories

NA: None applicable

Colors/Finishes Model Description K-5244-ER High Efficiency Urinal (HEU) 0 Other **Optional Accessories** 18773 3" outlet spud

Product Specification

The washout urinal shall be made of vitreous china with rear supply. Urinal shall have a 15-5/8" (397 mm) extended rim. Urinal shall use 0.125 gpf (0.47 lpf). Urinal shall include removable strainer, 2" outlet spud, universal mounting bracket, hangers, flexible supply hose, and 5/8" adapter. Urinal shall be WaterSense compliant when used with WaterSense flushometer. Urinal shall be Kohler Model K-5244-ER-

Specified Model

STEWARD_® HYBRID

Technical Information

Fixture:		
Configuration	Rear suppy urinal	
Water per flush	0.125 gpf (0.47 lpf)*	
* Designed to flush with 0.125 gpf (0.47 lpf) of water when installed with a water-saving flushometer.		
Included components:		
2" outlet spud		18766
Hanger (2 required)		64512
Universal mounting bracket		1044200
Removable strainer		1195702
Braided stainless steel hose, G1/2		1219185
5/8" adapter, male		1219296

Installation Notes

Install this product according to the installation guide.

Roughing-in remains the same when using the optional $3^{\prime\prime}$ outlet spud.

NOTICE: For ADA compliance, measurement must be from the floor to the top of the internal lip.

Will comply with **ADA** when installed per Section 605 Urinals of the 2010 ADA Standards for Accessible Design.

