

Lighting Your Life Since 1970

Product Specifications - 71150I			
Job Name:	Job Type:		
Quantity:	Comments		



Builder Basics 5-Light Chandelier

Finish Oil Rubbed Bronze

Lamping **Number of Bulbs**

Dimmable

Light Type	Incandescent
Bulb Type	CA
Max Bulb Wattage	60
Max Fixture Wattage	300
Rated Life	±1,500 Hours
Rated Lumens	±3,360
Color Temp	±2,700 K
Bulb(s)	Not Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A

_	I	10	I	-1

5

No

Standard Dimmer

Measurements

Wire Length

Canopy Width

Canopy Height

Canopy Length

Width	23.0"
Height	15.0"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	N/A
Max Overall Height	N/A
Hanging Weight	4.5 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	36"

Product Category

Single-Tier Chandelier

c	hi	n	n	in	\sim
-0	ш	v	IJΙ	ш	u

Snipping	
Carton Weight	4.5 lbs
Carton Width	24"
Carton Height	6"
Carton Length	24"
Carton Cubic Feet	1.91
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

Cert	tificat	tion	

Ballast/Driver/Transformer

Certification	,
UL Standard	Dry l
Energy Star	No S
CA Title 24	No (
CA Title 20	No I
ADA	No (
Dark Sky	N/A

Other		Equivalents	
UPC Code	783209711501	Incandescent Watts	N/A
Shades Included	N/A	Fluorescent Watts	N/A
Crystals Included	N/A		
Diffuser Included	N/A		
Conversion Kit	N/A		
Material	Iron		

180"

N/A

N/A

N/A

Maxim Lighting International and all designs, logos and images © 2013 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.