

Lighting Your Life Since 1970

Product Specifications - 60201CLPB		
Job Name:	Job Type:	
Quantity:	Comments	



60201CLPB

Bound Glass 9-Light Entry Foyer Pendant

Finish Polished Brass

Lamping

Number of Bulbs	9		
Light Type	Incandescent		
Bulb Type	CA		
Max Bulb Wattage	25		
Max Fixture Wattage	225		
Rated Life	±2,500 Hours		
Rated Lumens ±1,9			
Color Temp	±2,700 K		
Bulb(s)	Not Included		
Light Up/Down			
Beam Spread			
CRI	N/A		
Photo Cell Included	N/A		
Ballast/Driver/Transformer	No		
Dimmable	Standard Dimmer		

Glass/Shad	e
Clear	

Measurements	
Width	

Canopy Length

No Shades Included

No Crystals Included

Diffuser Included

Conversion Kit

Material

modean emente	
Width	16.5"
Height	32.5"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	N/A
Max Overall Height	N/A
Hanging Weight	22.5 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	36"
Wire Length	180"
Canopy Width	N/A
Canopy Height	N/A

Product Category

Entry Foyer Pendant

Shipping	
Carton Weight	22.5 lbs
Carton Width	21'
Carton Height	34'
Carton Length	22'
Carton Cubic Feet	8.94
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

Certification Safety Rating

Energy Star

CA Title 24

CA Title 20

Dark Sky

ADA

Other Dry UPC Code

No

No

N/A

Equivalents

N/A

783209000117	Incandescent Watts	N/A
N/A	Fluorescent Watts	N/A
N/A		
N/A		
N/A		
Copper		

Maxim Lighting International and all designs, logos and images © 2013 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.