

# INSTALLATION INSTRUCTIONS

For Model#4282 (Rev. 02/27/2012)

## READ AND SAVE THESE INSTRUCTIONS

**WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.**

**AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.**

1. Shut off the power at the circuit breaker and remove old fixture, including the crossbar.
2. Carefully unpack your new fixture and lay out all the parts on a clear area. Take care not to lose any small parts necessary for installation.
3. Place the circular strap (A) over the outlet box, the side of the circular strap (A) marked "GND" must face out. Hold it in place, secure to the outlet box by threading two screws (B) (Size: #8-32N\*L0.5") into the slotted holes. Thread two studs(C) into circular strap (A) to mount fixture onto.
4. At the point, connect the wires as follows; connect the black wire from the fixture to the black house (hot) wire. Connect the white wire from the fixture to the white (neutral) house wire. Make sure all wire nuts are secured. Wrap the connections with electrical tape. If your outlet has a ground wire (green or bare copper), connect fixture's ground wire to it. Otherwise connect fixture's ground wire directly to the crossbar using the green screw provided. (Fig.2)
5. After the wires are connected, tuck them carefully inside the outlet box as you place backplate (D) over two studs (C) through the holes. Secure backplate (D) against the wall by threading two cap nuts (E) tightly.
6. Install the bulbs in accordance with the fixture's specification. **(DO NOT EXCEED THE MAXIMUM WATTAGE RATING!!)** **(NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!).**
7. Slide shade (F) into the fixture carefully.

### MIN 90 SUPPLY CONDUCTORS

Your installation is now complete. Return power to the junction box and test the fixture.

**Note: Illustration (Fig. 1) on this manual is for installation purposes only. It may or may not be identical to the fixture purchased.**

