



Buy it for looks. Buy it for life.®

Specifications

FAUCET DESCRIPTION

- Metal construction with various finishes identified by suffix
- 1/2" IPS connections will accept standard ball nose connection for 3/8" tubing
- Includes matching finish side spray with Hydrolock® quick connect system

OPERATION

- Lever style handles
- Maximum handle rotation angle is 90° to full on for either handle. Rotate Hot side, counterclockwise to open (clockwise to close). Rotate Cold side, clockwise to open (counterclockwise to close)

FLOW

- Aerator is limited to 2.2 gpm (8.3 L/min).

CARTRIDGE

- 1224 cartridge design
- Nonmetallic, nonferrous and stainless steel material


STANDARDS

- Third party certified to meet CSA B125.1, ASME A112.18.1 and all applicable requirements referenced therein, including NSF 61/9
- Contains no more than 0.25% weighted average lead content
- Complies with California Proposition 65 and with the Federal Safe Drinking Water Act

- **ADA**  for lever handles

WARRANTY

- Lifetime limited warranty against leaks, drips and finish defects to the original consumer purchaser
- 5 year warranty if used in commercial installations




CASTLEBY™ Two-Handle Kitchen Faucet

Models: CA7905 series

CA7902 series (without side spray)

Bulk Models: CA67905
(packed 12 per carton)

NOTE: DESIGNED TO INSTALL THROUGH 4 HOLES,
1-1/4" (32MM) MIN. DIA. AND 4" (102MM) ON CENTER.



CRITICAL DIMENSIONS

(DO NOT SCALE)