

COTSWOLD™



15422 AGZ

COTSWOLD™



15420 AGZ

Ordering Guide & Finish	15422 AGZ	15420 AGZ
Housing	Cast Aluminum	Cast Aluminum with weathered white glass
Lamp Base	12V T5 wedge base socket	12V T5 wedge base socket
Supplied Lamp	11.6-W(VA) 912X (17023) Xenon light source Power usage at 12V AC input VA MAX: 16.25-W(VA)	11.6-W(VA) 912X (17023) Xenon light source Power usage at 12V AC input VA MAX: 16.25-W(VA)
Incandescent Lamp Options	16.25-W(VA) 921X (17025) 6.5-W(VA) 918X (17022) 4-W(VA) 901X (17021)	16.25-W(VA) 921X (17025) 6.5-W(VA) 918X (17022) 4-W(VA) 901X (17021)
LED Lamp Options	2W (18039-18041) see page 137. Compares up to 16W Xenon.	2W (18039-18041) see page 137. Compares up to 16W Xenon.
Wiring	26" of usable #18-2, SPT-1-W leads. Cable connectors supplied.	28" of usable #18-2, SPT-1-W leads. Cable connectors supplied.
Mounting Access. (Included)	8" In-ground slotted stake	8" In-ground slotted stake
Optional Accessories	15601 – Surface Mounting Flange 15607 – Surface Mounting Bracket	15601 – Surface Mounting Flange 15607 – Surface Mounting Bracket
Photometric with Supplied Lamp	Distance from Light	Distance from Light
	Foot Candles	Foot Candles