

# AirKing<sup>®</sup>

## Ventilation Products

SPECIFICATIONS  
**AKF80LS**  
 EXHAUST FANS

**80 CFM/0.8 SONES @ 0.10" WG.**  
**HVI CERTIFIED 120 Volts, 0.75 amps, 60 Hz.**

• **Grill**

White, polymeric grill secured in place with torsion springs; easily removed if necessary, dimensions - 11" x 13<sup>3</sup>/<sub>4</sub>". Moonstone glass lens.

• **Blower Wheel**

Balanced polymeric dual inlet blower wheel 5<sup>1</sup>/<sub>4</sub>" dia. x 2<sup>27</sup>/<sub>32</sub>" depth, 30 paddles, secured in place via press fit.

• **Motor**

Enclosed 4 pole electronically balanced permanently split capacitor motor (PSC); life time lubricated, suitable for continuous operation. Motor bearings - ball. Rated 115/120 volts, 60 Hz, 0.30 amps.

• **Fan Housing**

23 gauge galvanized steel housing. Overall dimensions 10<sup>7</sup>/<sub>8</sub>" x 9<sup>3</sup>/<sub>8</sub>" x 7<sup>7</sup>/<sub>8</sub>".

• **Duct Collar**


4" round, zinc plated metal collar adapter. 4" spring loaded aluminum backdraft damper.

• **Ventilating Area**

For bathrooms up to 80 sq. ft. For other rooms up to 100 sq. ft.

• **Electrical Connections**

1/2" electrical knockouts provided. Easy wiring access via either internal or external wiring compartment cover.



### CUL/HVI

Acceptable for use over tub or shower when installed in a GFCI protected branch circuit.

• **Lighting**

Electronic Quick Start Ballast – rated 26 Watt – Use Triple 4 pin PL lamp. Maximum 26 Watt.

• **Unit Mounting**

The housing will mount in ceilings with at least 8" of clearance and through drywall thickness up to 3/4", with a rough-in opening of 11<sup>1</sup>/<sub>8</sub>" x 9<sup>5</sup>/<sub>8</sub>". Rated for ceilings insulated to R-40. The housing will mount either between 16" or 24" on center joists, using the 4 supplied housing mounting rails. The housing mounting rails can be adapted for overhead mounting (hardware not provided).

• **Single Pack Shipping Info**

Box Dim Box Dim: 14<sup>1</sup>/<sub>8</sub>" x 11<sup>5</sup>/<sub>8</sub>" x 12"  
 UPC: 0-8316228051-0  
 Shipping Weight: 11.5 lbs.

PERFORMANCE											
	Static Pressure (inches of w.g.)								HVI Sones @ .1 SP	Fan Speed RPM	Power Watts
	0	0.05	0.1	0.125	0.15	0.2	0.25	0.3			
<b>Air Flow - CFM</b>	87	84	80	77	73	64	52	40	0.8	984	26

<b>PROJECT</b>							<b>ARCHITECT</b>				
<b>LOCATION</b>							<b>ENGINEER</b>				
<b>CONTRACTOR</b>							<b>SUBMITTED BY</b>			<b>DATE</b>	
FAN NUMBER	MODEL NUMBER	CFM	IN W.G.	RPM	WATTS	AMPS	SONES	QTY	OPTIONAL EQUIPMENT & REMARKS		



**U.S.:** 820 Lincoln Drive  
 West Chester, Pennsylvania 19380-4466  
 Tel: (610) 692-7400 • 877-304-3785  
 Fax: (610) 696-8048

**Canada:** 110 Glidden Road  
 Brampton, Ontario L6T 2J3  
 Tel: (905) 456-2033  
 Fax: (905) 456-1015