

12V LED/INCANDESCENT ACCENT

ADJUSTABLE WIDE FLOOD



15395 AZT

MINIATURE HOODED ADJUSTABLE WIDE FLOOD



15396 AZT

	15395 AZT	15396 AZT													
Ordering Guide & Finish	15395 AZT	15396 AZT													
Housing	Cast Aluminum. Heat-resistant flat glass is fully sealed.	Cast Aluminum. Heat resistant flat glass lens is fully sealed.													
Lamp Base	12V Incandescent bi-pin, high temperature porcelain socket	12V Incandescent bi-pin, high temperature porcelain socket													
Supplied Lamp	50-W(VA) QT4 (17015). Halogen light source.	35-W(VA) QT3 (17013). Halogen light source.													
Incandescent Lamp Options	Power usage at 12V AC input VA MAX: 75-W(VA) see page 140	Power usage at 12V AC input VA MAX: 35-W(VA) see page 140													
LED Lamp Options	N/A	N/A													
Wiring	35" of usable #18-2, SPT-1-W leads. Cable connectors supplied.	35" of usable #18-2, SPT-1-W leads. Cable connectors supplied.													
Mounting Access. (Included)	8" slotted in-ground stake	8" slotted in-ground stake													
Optional Mounting Accessories	15601 – Surface Mounting Flange 15607 – Surface Mounting Bracket 15609 – Junction Box Mounting Bracket 15647 – 90° Elbow 15649 – Stem Coupler 15645, 15656, 15657, 15658 or 15570 – Stems	15601 – Surface Mounting Flange 15607 – Surface Mounting Bracket 15609 – Junction Box Mounting Bracket 15647 – 90° Elbow 15649 – Stem Coupler 15645, 15656, 15657, 15658 or 15570 – Stems													
Notes	U.S. Patent D417,519. See page 171 for photometrics.	U.S. Patent Pending. See page 171 for photometrics.													
Photometric with Supplied Lamp			A	B	C	D	E	F		A	B	C	D	E	F
	3'	9.30	5.43	1.81	.9	.18	.09		3'	13.89	8.33	2.78	1.39	.28	.14
	4'	5.08	3.05	1.01	.51	.10	.05		4'	7.81	4.69	1.56	.78	.16	.08
	5'	3.25	1.95	.65	.33	.07	.03		5'	5	3	1	.5	.1	.05
	6'	2.26	1.35	.45	.23	.05	.02		6'	3.47	2.08	.69	.35	.07	.03
	7'	1.66	.99	.33	.17	.03	.03		7'	2.55	1.53	.51	.26	.05	.03
	8'	1.27	.76	.25	.13	.03	.01		8'	1.95	1.17	.39	.2	.04	.02
	9'	1	.6	.1	.1	.02	.01		9'	1.54	.93	.31	.15	.03	.02
	10'	.81	.49	.08	.08	.02	.01		10'	1.25	.75	.25	.13	.03	.01