


CATALOG NUMBER	TYPE
PROJECT	

4" LINE VOLTAGE DOWNLIGHTS

R-420



Ordering Matrix







Series	Model	Finish(Baffle/Trim)
[]	[]	[]
R	420	BK/WT BN BZ WT/WT

Ordering Example (series – model number – finish): R-420-BK/WT

Product Details	
Description:	Recessed trim with interior step baffle. For use with R-4XX series Line voltage downlights.
Materials:	Durable stamped metal construction. Fingered retention clips firmly hold trim to housing.
Lamping	Utilizes medium base incandescent or 4-pin CFL lamps. Incandescent lamps are rated for up to 50W watts max. Compact Fluorescent lamps are rated for 13 watts max. Lamps are ordered separately.
Finish:	Abrasion resistant powder coat painted or plated metal finish. Baffle is available in Black (BK), Bronze(BZ) , Brushed Nickel(BN) or White (WT) . Trim is available in Brushed Nickel (BN), Bronze(BZ) or White.
Listing:	UL & CUL Listed. Suitable for damp locations.

Specification Features
<ul style="list-style-type: none"> • Handles surfaces up to 1" • 5 year W.A.C. Lighting product warranty.

Compatible Housings(Sold separately)

<p>R-400S-N-A</p> <p>NON-IC Rated. Air tight. New Construction 50W PAR20; 50W R20</p>		<p>R-401S-R-A</p> <p>NON-IC Rated. Air tight. Remodel housing 50W PAR20; 50W R20</p>	
<p>R-402S-N-ICA</p> <p>IC Rated. Air tight. New Construction 50W PAR20; 50W R20</p>		<p>R-F404S-R-ICA</p> <p>IC Rated. Air tight. Remodel housing 13W Max. CFL</p>	
<p>R-F403S-N-ICA</p> <p>IC Rated. Air tight. New Construction 13W Max. CFL</p>		<p>R-F406S-R-A</p> <p>NON-IC Rated. Air tight. Remodel housing 13W Max. CFL</p>	
<p>R-F405S-N-A</p> <p>NON-IC Rated. Air tight. New Construction 13W Max. CFL</p>	