

1215WC • 15" Wine Captain® Model • 1000 Series









INTEGRATED FRAME



BLACK FRAME

FEATURES & BENEFITS

PERFORMANCE

- Volume of 2.9 cu ft holds up to 24 wine bottles (750 ml)
- Digital Touch Pad Control is conveniently located on upper face of unit
- Temperature range: 38°F 65°F
- Passive cooling system
- Rubber mounted compressor virtually eliminates vibration

INTERIOR/EXTERIOR

Black interior is illuminated with LED lighting that automatically turns off when the door is closed, or can be set to stay on for 3 hours

- Three-quarter extension black vinyl wine racks with natural beech wood fronts allow for easy access and prevent bottles from shifting
- Wine racks accommodate a variety of bottle shapes and sizes, while the fourth and fifth racks allow for larger diameter wine and champagne bottles
- LowE coated, argon gas filled, dual thermopane glass door provides protection from harmful UV light
- Standard commercial stainless steel handle is interchangeable with professional handle accessory
- Door swing is field reversible

INTEGRATION

- Unit is designed to be built-in or can be freestanding
- Solid natural beech wood fronts on wine racks can easily be stained to match surrounding cabinetry
- Integrated model requires ³/₄" custom door panel (panels not supplied by U-Line)
- Four independently adjustable leveling legs provide a precise undercounter fit
- Available in the following finishes: Stainless, Integrated, or Black

MODEL DETAILS

Model	Voltage/Hz	Door Swing	Finish	Shipping Weight
U-1215WCS-00B	115 / 60	Field Reversible	Stainless Frame	102 lb
U-1215WCINT-00B	115 / 60	Field Reversible	Integrated Frame	99 lb
U-1215WCB-00B	115 / 60	Field Reversible	Black Frame	102 lb

ACCESSORIES


Model	Description	Finish	Shipping Weight
80-54247-00	Professional Door Handle, 1 1/4" Diameter	Stainless	2 lb
80-54214-00	Commercial Door Handle, 7/8" Diameter	Stainless	2 lb




1000 Series • 15" Wine Captain® Model • 1215WC

DIMENSIONS

Dimensions shown apply to all finishes, including Integrated (INT) models with 3/4" integrated panel/frame installed.



CABINET CUT-OUT



SPECIFICATIONS

Model	1215WC	
Amps: Running	1.2	
Capacity: Volume (cu ft)	2.9	
Capacity: Wine Bottle (750 ml)	24	
Control Type	Digital Touch Pad	
Dimensions: Product Depth	23 ½" / 591 mm	
Dimensions: Product Height	34 ½" / 867 mm	
Dimensions: Product Width	14 ¹⁵ / ₁₆ " / 379 mm	
ENERGY STAR	N/A	
Panel Height	30 ½" / 768 mm	
Panel Thickness	3/4" / 20 mm	
Panel Type	2 ¾" / 70 mm Frame Panel	
Panel Width	14 ³ / ₄ " / 375 mm	
Product Weight: Max	95 lb	
Refrigerant Type	R600a	
Sabbath (Star K Certified)	Yes	
Temperature Range	38°F - 65°F	

INSTALLATION NOTES

When installing adjacent to wall, ensure 2 $^{1}2''$ clearance on hinged side for 90 $^{\circ}$ door opening

Cutout includes the additional $\frac{1}{4}$ " width overall to ensure proper installation.

No additional clearance around sides, top or rear of unit is needed for ventilation.

Do not obstruct front grille air flow.

COOLING SYSTEM



ELECTRICAL REQUIREMENTS

This unit requires a grounded, polarized 115 VAC, $60\,Hz$, $15\,A$ power supply (normal household current).





Residential & Commercial

Please visit U-Line.com to view this model's User Guide. All specifications are subject to change without notice.